

AZYC.AU5233 - AUTOMOTIVE BOOSTER CABLE

Automotive Booster Cable

See General Information for Automotive Booster Cable

NINGBO LINSHENG ELECTRIC CO LTD

XIAODONG INDUSTRIAL PARK

YUYAO, ZHEJIANG 315408 CHINA

Automotive Booster Cable Assembly Models: LBU01: 2AWG, 6AWG, 4AWG, 8AWG; LBU03: 10AWG

AU5233

AWG	Length (ft)	Clamp Style	Current Rating (A)	Temp Rating (°C)
2 (Copper Wire)	20	C1	500	-40
2 (Copper Clad Aluminum Wire)	20	C1	450	-40
4 (Copper Wire)	20	C1	325	-40
4 (Copper Clad Aluminum Wire)	20	C1	275	-40
6 (Copper Wire)	16	C1	300	-40
6 (Copper Clad Aluminum Wire)	16	C1	250	-40
8 (Copper Wire)	12	C1	230	-40
8 (Copper Clad Aluminum Wire)	12	C1	200	-40
10 (Copper Wire)	12	C2	150	-40
10 (Copper Clad Aluminum Wire)	12	C2	100	-40

Last Updated on 2012-08-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

Contact: Tom shen Email: powersupplycord@gmail.com