



ELBZ8.E257089 - CORD SETS AND POWER-SUPPLY CORDS CERTIFIED FOR CANADA - COMPONENT

Cord Sets and Power-supply Cords Certified for Canada - Component

See General Information for Cord Sets and Power-supply Cords Certified for Canada - Component

NINGBO XUANHUA ELECTRIC CO LTD
 SIMEN TOWN
 YUYAO, ZHEJIANG 315472 CHINA

E257089

Power-supply Cord Cat. No.	Cord or Wire AWG Size	Electrical Rating (Amps/Volts)	Code
XIP-A	18	10/125,250,300,600	d
	16	13/125,250,300,600	d
	14	15/125,250,300,600	d
	12	20/125,250,300,600	d
	10	30/125,250,300,600	d
XIR-A	18	10/125,250,300,600	d
	16	13/125,250,300,600	d
	14	15/125,250,300,600	d
	12	20/125,250,300,600	d
	10	30/125,250,300,600	d
XIP-B	18	10/125,250,300,600	d
	16	13/125,250,300,600	d
	14	15/125,250,300,600	d
	12	20/125,250,300,600	d
	10	30/125,250,300,600	d
XIR-B, XM-04,	18	10/125,250,300,600	d
	16	13/125,250,300,600	d
	14	15/125,250,300,600	d
	12	20/125,250,300,600	d
	10	30/125,250,300,600	d

Contact: Tom shen Email: powersupplycord@gmail.com

	10	30/125,250,300,600	d
XIR-B2	18/3	10/125, 250, 300, 600	b, d
	16/3	13/125, 250, 300, 600	b, d
	14/3	15/125, 250, 300, 600	b, d
	12/3	20/125, 250, 300, 600	b, d
Strain Relief Bushing Cat. Nos. XK01, XK02	18, 16, 14 AWG SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW	—	—
XIP-C	18	10/125, 250, 300, 600	d
	16	13/125, 250, 300, 600	d
	14	15/125, 250, 300, 600	d
	12	20/125, 250, 300, 600	d
	10	30/125, 250, 300, 600	d
XN515R-C	18	10/125	d
XN520R-E3	14(AWM Style 22094 , ST, STW, STO, STOW, STOO,STOOW, S, SO, SOW, SOO, SOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SJ, SJO, SJOW, SJO, SJOOW)	18/125	d
	12(AWM Style 22094)	20/125	d
	10(AWM Style 22094, ST, STW, STO, STOW, STOO,STOOW, S, SO, SOW, SOO, SOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SJ, SJO, SJOW, SJO, SJOOW)	20/125	d
XN115R-A	18/2, SVT, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-1W, SPT-2W	10/125	d
	16/2, SVT, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2W	13/125	d
	14/2, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW	15/125	d
XN550R-A	10/3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJO, SJOOW, S, SO, SOW, SOO, SOOW	30/125	d
	8/3, ST, STW, STO, STOW, STOO, STOOW, S, SO, SOW, SOO, SOOW	40/125	d
XN1420R-A	14/4, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJO, SJOOW, S, SO, SOW, SOO, SOOW	18/125,250	d

Contact: Tom shen Email: powersupplycord@gmail.com

	12/4, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO, SOOW	20/125,250	d
	10/4, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO, SOOW	20/125,250	d
XN615R-A	14/4, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO, SOOW	15/125	d
	12/4, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO, SOOW	15/125	d
	10/4, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO, SOOW	15/125	d

Codes:

- a - The strain relief bushing, if provided at the free end of the power-supply cord, has been investigated for 13.6 kg.
- b - The flexing relief bushing, if provided at the free end of the power-supply cord, has not been investigated.
- c - The suitability of the terminals, if provided as part of the power-supply cord, has not been investigated.
- d - The flexible cord or wire type and the ampacity of the cord or wire has not been investigated for use in specific equipment.

Marking: Company name or trade name or trademark, catalog designation and the Recognized Component Mark for Canada



Last Updated on 2019-03-07

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"